


The $D_2^{\mathbb{M}}$ is a passive laser warning receiver that features a higher wavelength band of detection than its predecessor the $D_1^{\mathbb{M}}$. It detects and coarsely locates laser emissions from other hunters' laser devices and rangefinders. The device enhances safety and survivability for today's battlefield environment by notifying an operator of any and all classes of commercial and military laser devices. $D_2^{\mathbb{M}}$ will alert its wearer of laser emissions through selectable audible, visual, and tactile feedback. It can also be connected to a management system and provide laser warning as a defensive aid via USB C port. The $D_2^{\mathbb{M}}$ is tuned to minimize false alarms while maintaining an ultra-fast response time of less than 50 milliseconds. The system can be worn anywhere on the body; typically, on the chest or back or attached to a helmet.

Detection Range	up to 1 km for commercial LRF up to 2 km for military LRF
Field of View	210° horizontal x 120° vertical
Frequency Range Detection	750 to 1700 nm
Detection Direction	Left, Center, Right
Detection Notification	LED, sound and vibration
Power	2 x CR123 batteries or USB
Working Time on Battery	8 hrs
Size	101 x 65 x 32 mm
Weight	110 g w/ battery
Mounting	Velcro strap or 1/4-20 tripod mount



BENEFITS AT A GLANCE

 $D_{2x^{\text{TM}}}$ system is designed as a body-mounted aid to warn the user of a laser event alarms caused by:

- · Laser rangefinder systems, both commercial and military
- UAV (drone) ranging equipment
- Handheld and rifle mounted NVG illuminators and pointers
- Variety of visible and invisible laser markers and designators used in the battlefield environment
- Mitigate friendly fire incidents by alerting the user of a laser illumination



