

G1™ 1-8x24 Riflescope

Internal Display Technology (ID)



G1™ ID is the first product with unique Internal Display technology. The ID does not interfere with any standard function of the 1-8 x 24 riflescope. With sensor technologies G1™ can vastly expand the utilization of the riflescope by offering *Situational Awareness* while user is focused on the target.

The G1™ riflescope offers the following features:

- State-of-the-art optical coatings offer anti-reflective low light performance
- Second focal plane reticle maintains the same appearance throughout the power range
- Glass-etched illuminated reticle with brightness control for low light conditions
- Tube size is standard 30 mm diameter

Specifications

Magnification	1-8x
Objective Lens Diameter	24 mm
Exit Pupil	9-3 mm
Eye Relief	35 in / 89 mm
Diopter Adjustment	±4
Field-of-View	116.5-14.4 ft / 100 yds
Field-of-View	38.6 – 4.7 m / 100 m
Tube Diameter	30 mm
Turret Style	Capped, Finger Adjusted
Click Value	1/2 MOA
Elevation Adjust. Range	45 MOA
Windage Adjust. Range	45 MOA
Parallax Setting	100 yds
Size (L x W x H)	10x3x3 in / 254x76x76 mm
Weight	23 oz / 652 g
Picatinny Mount Height	1.5 in / 38.1 mm
Illuminated Reticle Battery	CR2032
Internal Display	Monochrome Yellow OLED
Display Interface	Special USB
Environmental	IP67



Internal Display is a Registered Trademark of Torrey Pines Logic, Inc. Patents pending for ID, G1 and T series and its components

